

For more information on compatible hardware, please, contact the following companies:

Hoppe North America, Inc.

205 East Blackhawk Drive
Fort Atkinson, WI 53538
HLS 9000 Swing Door Handles -
Dallas or Munchen series
Phone (920) 563-2626
Website:
<https://www.hoppe.com/us-us/door-handles/>

Hewi, Inc.

Harbor City Supply
Lutherville Timonium, MD 21093
(443) 279-0632
Website:
<https://www.harborcitysupply.com/hewi-door-hardware/>

Bouvet

540 DeHaro Street
San Francisco, CA 94107
Phone (415) 864-0273
Fax (415) 864-2068

Rocky Mountain Hardware

1020 Airport Way
Hailey, ID 83333
Phone (888) 788-2013
Website:
<https://www.rockymountainhardware.com/contact/find-dealer/>

FSB - North America

Berlin, CT 06037
Contact:
<https://www.fsbna.com/us/support-and-resources/sales-representative/>

Valli & Valli (U.S.A.) Inc.

150 E. 58th, 4th FL
New York, NY 10155
Phone (877) 326-2565
Fax (212) 326-8816

Please note that most of the catalogs of the above companies do not show matching window handles. As these handles are not common usage here, they are not stocked in the U.S. However, as most lever handles do have matching window handles available in Europe, matching handles can usually be specially ordered.

Use of Handles and Escutcheon Plates from Other Suppliers

Although availability may be restrictive and limited, other compatible handles and escutcheon plates can be used in place of the handles and escutcheon plates provided with the units. If other escutcheon plates are planned to be used, Nana Wall Systems must be notified when placing an order.

With Multi Point Locking with Latch, Deadbolt and Top/Bottom Locking Rods

In place of standard lever handles on the swing panel, any European specification lever handle with an 8 mm (5/16") spindle can be used. However, only escutcheon plates with the following specifications can be used:

The base width must be less than 1 1/4" (32 mm).

The distance between the center of the spindle hole and the center of the lockset must be the European standard of 3 5/8" (92 mm).

For escutcheon plates that are attached with screws from the inside to the outside, the trim plate length must be such that the distance between the center point of the two screw holes is at least 7 7/8" (200 mm).

With Two Point Locking

Inward Opening Units: In place of standard handles that operate the two point locking, any European specification window handle with a 7 mm (9/32") spindle can be used, provided that the rosette base is less than 1 1/4" (32 mm). Note, however, that the folding stack may not be as flat a stack as with NanaWall standard handles.

Outward Opening Units:

In place of standard handles that operate the two point locking, only a European specification window handle with a protrusion of less than 3/4" (19 mm), with a 7 mm (9/32") spindle, and with a rosette base of less than 1 1/4" (32 mm) can be used